



INTERNATIONAL

www.kshinternational.com

Speciality Products



Typical Applications

- ⌘ Power Transformers
- ⌘ HVDC Transformers
- ⌘ Generator Transformers
- ⌘ Traction Transformers
- ⌘ Electrical Rotating Machines
- ⌘ 765 Kv Transformers and Reactors
- ⌘ 1200 Kv Transformers

Speciality Products

Twin, Triple, upto Six Conductors Bunch Winding Wire for Power Transformers (Axial & Radial) with Epoxylite® option available

Typical Advantages

- ✕ Better space factor
- ✕ Better heat dissipation
- ✕ Higher dielectric strength
- ✕ Higher thermal stability
- ✕ Higher mechanical strength of the insulation
- ✕ Higher thermal overload capacity
- ✕ Easier to process than paper insulated conductors of the same section
- ✕ Reduces eddy current losses

Proof Stress Copper Winding Wire to improve short circuit strength of wound coils

Typical Advantages

- ✕ CPR 1: 140 N/mm² - 200 N/mm²
- ✕ CPR 2: 170 N/mm² - 220 N/mm²
- ✕ CPR 3: 220 N/mm² - 260 N/mm²

CTC with Epoxylite® Coating and Netting Tape

Typical Advantages

- ✕ High short circuit force stability
- ✕ Partial Discharge (PD) free for applications in interleaved type windings
- ✕ Lower losses in Transformers



Combinations of Enamel + Nomex®

Enamel + Paper Insulated with Glued Nomex® Strip between strand

Copper Strip Enamelling



Laser Dimensional Controls & Burr Detection



Inline Fault Detectors



Precise Corner RADII



Rolling Mill



Quality Control Of Critical Parameters

